

FASTER

WHOELSE?

LGA775
Intel Pentium 4



Dual DDRII x 4



PCI Express



Duo ODDs



SRS  **WOW** is a trademark of SRS Labs, Inc.

PIONEER

D900T Specification



PIONEER

Model	D900T
CPU	Intel® Pentium® 4 Processor 520/530/540/550/560/570 with HT Technology (2.80~3.80 GHz, 90nm, FSB800, 1 MB L2 cache, LGA775)
Core Logic	Intel® 915P + ICH6
Display	17.1" WXGA (1440x900) TFT / 17.1" WSXGA+ (1680x1050) TFT
Memory	Two 64-bit wide DDRII data channels Four 200-pin SODIMM sockets, supporting DDRII 400/533 Expandable Memory up to 4GB, 2814MB available, based on 256/512/1024MB SODIMM Module
Video Controller	ATI® Radeon™ X800 High performance graphics chip 256MB DDRIII Video RAM on board 128bit graphic engine PCI-Express x16 Fully DirectX® 9.0 support
Storage	One changeable Primary 2.5" HDD 9.5mm(H) (Option) One changeable Secondary 2.5" HDD 9.5mm(H) Serial ATA HDD support One changeable Primary Bay for 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive (Option) One changeable Secondary Bay for 12.7mm(H) CD-ROM / DVD-ROM / Combo / DVD-Dual Drive (Option) One external USB 1.44MB Floppy Disk Drive Supporting Master mode IDE ATA-100/133 (Ultra DMA)
Keyboard	Full size keyboard, with Numeric Pad, Multi-Language support Built-in Touchpad with scrolling function
Sound System	Intel® Azalia Compliant Interface 3D stereo enhanced sound system Virtual 8-channel audio output Sound-Blaster PRO™ compatible S/PDIF Digital output (5.1 CH) SRS (Sound Retrieval System®) / WOW 3D sound technology 1x Built-in Microphone 4x Built-in Speakers 1x Built-in Sub woofer 1x Built-in Audio DJ Console for music CD (MP3 format compatible)
I/O Ports	4x USB 2.0 ports 2x Mini IEEE1394a ports 1x S-Video jack for TV output & HDTV output 1x Serial port 1x Parallel port (LPT1), supporting ECP/EPP 1x Infrared Transfer port 1x DVI port 1x PS/2 port 1x Headphone jack 1x Microphone jack 1x S/PDIF output jack 1x Line-in jack for Audio input 1x RJ-45 port for LAN 1x RJ-11 port for Modem 1x DC-In jack 1x CATV input jack (optional function with TV-Tuner module) 1x S-Video jack for Video input (optional function with TV-Tuner module) Embedded 7-in-1 Card Reader (MS/MS Pro/SD/MMC/CF/SM/MicroDrive)
Card Reader	1x Type II PCMCIA socket
PCMCIA	Infrared Transfer : 115.2Kbps SIR/4Mbps FIR, IrDA 1.1 compliant
Communication	10/100/1000BASE-T Fast Ethernet onboard Integrated V.90/56K Azalia Modem (V.92 compliant) (Option) 802.11b/g MiniPCI Wireless LAN Module (Option) Bluetooth™ Class II V1.2 Module, MiniPCI interface, combo with WiFi Module (Factory option) 300K-pixel Video Camera module
Power Management	Full Range 180W AC adapter - AC input 100~240V, 47~63Hz, DC output 20V, 9A Changeable 12-cell Smart Li-Ion battery pack, 6600mAh
Security	Kensington® Lock
Dimension	397(W) x 298(D) x 49.5(H)mm, 15.6"(W) x 11.7"(D) x 1.9"(H) 5.8Kg with 12 cells Lithium-ion battery
Options	One changeable Second 2.5" HDD 9.5mm(H) One changeable Second Combo / DVD-Dual Drive 12.7mm(H) One external USB 1.44MB Floppy Disk Drive TV-Tunver, MiniPCI interface 802.11b/g MiniPCI Wireless LAN Module Bluetooth™ Class II V1.2 Module, MiniPCI interface, combo with 802.11b/g Wireless LAN Module One external USB 1.44MB Floppy Disk Drive (Factory option) 300K-pixel Video Camera module